



## 1000 Series

### RATINGS

		Input Torque Gross N•m (lb-ft)	Input Power Gross <sup>1</sup> Kw (hp)	Turbine Torque Net <sup>2</sup> N•m (lb-ft)	GVW kg (lbs)	GCW kg (lbs)
1000	General	780 (575)	224 (300)	1152 (850)	9000 (19,850)	11,800 (26,000)
	Refuse, On-Highway,	746 (550)	224 (300)	1152 (850)	7500 (16,540)	7500 (16,540)
	Transit Bus, Shuttle Bus, Coach, Non-North America School Bus	610 (450)	149 (200)	1017 (750)	7500 (16,540)	7500 (16,540)
1000 MH	Motorhome	746 (550)	224 (300)	1152 (850)	11,800 (26,000)	10,000 (22,000)
1000 SP	Specialty Vehicles	CONTACT YOUR ALLISON REPRESENTATIVE FOR DETAILS				

1. Gross Power rating as defined by ISO 1585 or SAE J1995. 2. Turbine Torque limit based on iSCAN standard deductions.

### DRIVETRAIN INTERFACES

Acceptable full-load engine governed speed	2200 – 4600* rpm
Acceptable engine idle speed range (with transmission in Drive)	500 – 820 rpm
Maximum output shaft speed at 105 km/hr (65 mi/hr)	5000 rpm

\* Engines with full load governed speed greater than 3200 rpm require Application Engineering review

### MOUNTING

To Engine	SAE No.3, SAE No.2
-----------	--------------------

### TORQUE CONVERTER

**Type** One stage, three element, polyphase.  
Includes standard integral damper which is operational in lockup.

Model	Stall Torque Ratio
TC-210	2.05
TC-211	1.91
TC-221	1.73
TC-222	1.58

### MECHANICAL RATIOS (Gear ratios do not include torque converter multiplication)

#### Range

First	3.10 : 1
Second	1.81 : 1
Third	1.41 : 1
Fourth	1.00 : 1
Fifth	0.71 : 1
Sixth*	0.61 : 1
Reverse	-4.49 : 1

\* Sixth speed available July 06 for specific vehicle configurations

### CONTROL SYSTEM

<b>Description</b>	Allison 4th Generation Electronic Controls with closed loop adaptive shifts
<b>Shift Sequences</b>	[C = Converter mode (lockup clutch disengaged); L = Lockup mode (lockup clutch engaged)]  Option 1: 1C-[1L]-2C-2L-3L-4L-5L Option 2: 1C-[1L]-2C-2L-3L-4L-5L-6L
<b>Driver-to-Transmission Interface</b>	Cab-mounted shift selector
<b>Communication Protocol - Engine/Vehicle Systems Interface</b>	SAE J1939, SAE J1587, ISO 9141, IESCAN

**PHYSICAL DESCRIPTION**

	Installation Length*	Dry weight	Depth below transmission centerline	
			With Shallow Oil Sump (Standard)	With Deep Oil Sump (Optional)
SAE No.3	729 mm (28.7 in)	150 kg (330 lbs)	272 mm (10.71 in)	284.9 mm (11.22 in)
SAE No.2	739 mm (29.1 in)	150 kg (330 lbs)	272 mm (10.71 in)	284.9 mm (11.22 in)

\*Approximate length from engine housing to output flange (depending on output flange type)

**TURBINE-DRIVEN POWER TAKE-OFF PROVISION**

PTO drive	Torque converter turbine-driven spur gear
PTO mounting pads	Six-bolt, 3 o'clock and 9 o'clock positions (as viewed from rear)
PTO drive gear rating (continuous operation)	Using one PTO: 339 N•m (250 lb-ft) Total using two PTO's: 271 N•m (200 lb-ft)
PTO drive gear ratio	1.00 x turbine speed
PTO drive gear	64 tooth

**PARK PAWL\***

\*Excluding refuse vocation

**OIL SYSTEM**

Oil type	Transynd™, DEXRON®-III
Capacity, excluding external circuits	
With Deep Oil Sump	18 litres (19 quarts)
With Shallow Oil Sump	16 litres (17 quarts)
Spin on canister filter	Standard

**SPEEDOMETER PROVISION**

Description	Non-zero-crossing square wave
8, 16 or 40 pulses per revolution of transmission output shaft	
Location	Electronic output from TCM

**TACHOGRAPH PROVISION**

Tone wheel	6-tooth
Mounting	M18 x 1.5 metric thread
Location	Transmission rear cover

**1000 Series**